

STREET STOCK 4CYL, 6CYL, FWD MINI-VAN AND POWDER PUFF RULES

These rules are plain and simple, cut and dry!!! What is said below is exactly what you can do and nothing else. Don't try and do anything else cause most likely you will just be loaded! Cars must remain completely stock other then what is listed, this meant to be an easy cheap to run class.

For questions contact Dan Hanson (563) 422 7095

Personal Protective equipment-

- Must have working seatbelt
 - Must have full face helmet
 - Clear or tinted safety glasses
 - Fire resistant long sleeve clothing is recommended
 - Long sleeve shirt, no t-shirt
 - Close toed shoes are required
 - Long pants are required, no shorts
1. Car must be stripped of all internals and outside plastic as well as all windows. Dash may stay in the car.
 2. NO CARB CONVERSIONS! **Motor must be from factory to that car.** No swapping.
 3. May chain motor/transmission mounts but no solid mounts, do not chain and then weld links or you will cut. Do not excessively wrap chain to try and strengthen frame, this is only to help hold mounts and if you do so trying to strengthen car you will cut.
 4. Factory steering, peddles, shifters, cables etc. must be to that car no aftermarket stuff.
 5. All suspension compents must remain stock no reinforcing of any components.
 6. All cars must have working brakes
 7. Trailer hitches and spare tires must be removed
 8. Roof Sign Required
 9. No Body Shaping

10. No rust repair allowed

11. Exhaust stacks are allowed

FWD cars 112" and under wheelbase, RWD drive cars 106" and under. Uni-Body cars only nothing full frame. Vans are FWD only, all wheel drive may run with rear driveshaft removed.

CAGE

- Full 4 point cage MUST be applied to your car for drivers safety must be floating, no down bars, (MINIMUM OF SEAT AND DRIVERS DOOR BAR) 3x3 material no bigger. Tank can be mounted to back of seat bar or may bolted through floor. IF IN FRONT OF REAR AXLE CAN BE LEFT UNDER CAR. If mounting tank on back of seat bar, mount can be no wider than 24 inches and has to be a minimum of 5" from floor and back seat pan area. May run a halo bar but can only attach to seat bar and cannot angle back in any way. May be bolted to roof in two locations. Cage in this class is for safety only, cannot reinforce car in any way other than driver safety.
- Battery must be moved inside vehicle and securely attached to floor.
- 2 front windshield bars **must** be added. 9 wire, 2x2 straps or chain
- No rear window bars.

DOORS, HOOD, TRUNK

- Drivers door may be welded shut. Every other verticle door seam can have 3 spots of 9 Wire double wrapped, chain single wrapped or 2"x2" by 1/8" plates.
- Hood and Trunk must have 12"x12" hole in them.
- Hood must remain on factory hinges.
- 2 allthread may run through your front core support mount up through hood to secure hood. No bigger than 3/4" allthread. hood washers can not exceed 5" by 5" by 1/4". May have a free floating washer on bottom and top of frame for threaded rod, washer cannot exceed 3' by 3" by 1/4"
- May tuck trunk lid but 60% of lid must stay in stock location. May also dish lid but must remain 10" of trunk floor. Cannot alter quater panels or speaker deck in any way must remain completely in stock location.
- Hood and trunk may have a total of 6 tie down spots each consisiting of the above methods.
- May have 2 strands of #9 wire per window opening double looped. Can only be in window opening I.e. **cannot** go from top of window opening to floor.

- No duck tape on doors

BUMPERS

Factory Car bumper stuffed and seam welded ok OR a 3"x3" by ¼" inch tube may be used for a bumper that is it. No points allowed on homemade bumpers.

You may use a 5 inch piece of 3"x3" square tube or a 3"x5" by 1/4" plate, one side of frame only, to mount bumper so bumper does not fall off. Nothing else. These are the only 2 style of bumper brackets that may be used.

Cars may be hardnose to front of the core support i.e. crush boxes on w body gm can be cut off. You may NOT relocate the core support in any way or you will be automatically loaded!

Rear bumper must remain stock or be removed, front bumper bracket rule does NOT apply it must remain stock.

TIRES

Any wheel and tire combo